



TECHNICAL DATA SHEET

Silicone Oil

APPLICATION:

Silicone oil is used for maintenance and assembly of moving parts. It is ideally suited for maintenance of bearings, transmissions, armoured cables, locks, sleeves, hinges and bolts, as well as rubber gaskets, shock absorbers and plastic parts. It makes easier assembly works that involve pulling through wires and cables or removing moulds in plastics processing. Useful for fishing equipment and in model-making, it also provides effective protection for electrical cables.



EFFECTS:

- Effectively penetrates hard-to-reach places;
- Makes easier to remove and pull through items;
- Prevents friction and jamming of plastic and rubber parts;
- Protects against moisture;
- Protects against short circuits and electric breakdown;
- Forms an anti-stick coating that protects against pollutants.

PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol
Colour:	Colourless
Odour:	Characteristic
Melting/Freezing point:	-35°C to -50°C
Initial boiling point:	> 250°C
Ignition temperature:	< 0°C
Flammability (solid, gas):	Extremely flammable
Upper/Lower explosive limit:	8.4%/1.8% vol. (propellant)
Density (20°C):	0.970 g/cm ³
Solubility:	Insoluble in water, soluble in organic solvents
Explosive properties:	Forms explosive mixtures with air
Oxidising properties:	Does not show



ECOLOGICAL INFORMATION:

The product is not classified as hazardous to the environment. No bioaccumulation is to be expected. The product has low mobility in aquatic environment and soil. Gas components quickly spread in the air.

STABILITY AND REACTIVITY:

The product is reactive and hazardous polymerization does not occur. Vapours may form explosive mixtures with air. If the product is heated > 150°C, trace amounts of formaldehyde may be released.

HEALTH AND SAFETY

Observe the general safety and hygiene rules. Avoid contact with eyes and skin. Remove immediately contaminated clothing. In the workplace, general and/or local ventilation should be provided to maintain the concentration of the harmful agent in the air below established limit values.

Keep away from children. Do not pierce or burn, even after use.

STORAGE:

Store only in dry and well-ventilated place below 50°C. Keep away from sources of fire and heat. Do not smoke and do not use open flames or sparking tools in the warehouse. Provide explosion-proof ventilation. Keep away from food, foodstuffs and animal feed. Protect from direct sunlight.

TRANSPORT:

The mixture poses no threat to the environment according to the criteria set out in the transport regulations. Packages shall not be thrown or subjected to impact. Containers/multi-packs should be placed on the vehicle or in the shipping box in such way to prevent them from falling down or dropping. Avoid heat sources.

NOTES: